



Shown with  
Optional  
Prison  
Package

**CONSTRUCTION:**

- Welded stainless steel
- Fully insulated
- Control panel accessible through front of unit
- Heating elements accessible inside of cabinet

**CONTROLS:**

- Mechanical controls
- Indicator light for thermostat
- Separate heat and humidity controls

**DOOR SWING:**

- Cabinet: 27-1/4"
- Hold open beyond 90 degrees
- Self closing within 90 degrees

**CLEARANCE:**

- Allow four inches on each side and back of unit

**SERVICE CONNECTIONS:**

- 7500-H-UA13T is equipped with a 20 Amp, nine foot, power cord. NEMA 5-20P plug.
- 120 Volt single phase is standard.

**SHIPPING WEIGHT:**

- 525 Pounds, FOB Menominee, MI 49858

**DIMENSIONS:**

|          | Height  | Width   | Depth   |
|----------|---------|---------|---------|
| Exterior | 73-1/2" | 29-3/4" | 34"     |
| Interior | 57-1/2" | 21"     | 29-1/2" |

**CAPACITY:**

|         | 18"x26"<br>Sheet Pans | 13"x18"<br>Sheet Pans | 12X20 Food<br>Service Pans | Spacing |
|---------|-----------------------|-----------------------|----------------------------|---------|
| Proofer | 13                    | 26                    | 26                         | 3"      |

**ELECTRICAL: Watts: 1700**

| Amp Draw | 120/1 | 120/208/3 | 120/240/1 | 120/240/3 |
|----------|-------|-----------|-----------|-----------|
| L1       | 16    | n/a       | n/a       | n/a       |

**7500-H-UA13T  
Stainless Steel Insulated  
Full Size, Universal  
STANDARD FEATURES:**

- Stainless steel construction
- Insulated solid door
- Casters
- Silicone rubber gasket on door

**OPTIONS:**

- Prison Package (Order as 7500-H-UA13TFL)
- Pass thru (order as 7500-H-UA13TP)
- Pass thru w/prison package (7500-H-UA13TFPLP)

