

RA-5T/RM-5T Tabletop Convection Oven



CONSTRUCTION:

- Welded stainless steel
- Fully insulated
- Control panel accessible through front and side of unit
- Heating elements accessible inside of cabinet and through side

RM-5T CONTROLS:

- Solid state controls
- Indicator light for thermostat
- Microswitch fan motor cut-off

RA-5T CONTROLS:

- Programmable controls
- 3 speed fan
- Microswitch fan motor cut-off

DOOR SWING: Oven - 30-1/2" (775 mm)

SERVICE CONNECTIONS:

- Unit is shipped from factory to be hard wired on site. Single phase uses three wire system. Three phase uses four wire system.

SHIPPING WEIGHT:

400 Pounds (159 Kg), FOB Menominee, MI 49858

RA-5T/RM-5T Convection Oven

STANDARD FEATURES:

- V-Air® technology
- Stainless steel construction
- Stainless steel legs (6")
- Cool to touch, dual pane, full view tempered glass door
- Field reversible doors
- Silicone rubber gasket on door
- Slam Cam handle
- Steam vent
- Tool-less cleaning of door glass

OPTIONS:

- Internal Steam
- Pass Thru
- Cook'n Hold
- Two Speed Fan
- Cart with Panslides (98-0350-PS)
- Cart without Panslides (98-0350-NP)
- Stand with Panslides (98-0351-PS)
- Stand without Panslides (98-0351-NP)
- Stacking Kit

DIMENSIONS:

	Height	Width	Depth
Exterior	41-3/4"	30"	37-13/16"
Interior	22"	18-3/4"	29-3/4"

CAPACITY:

	18"x26" Sheet Pans	13"x18" Sheet Pans	Spacing
Oven	5	10	4"

ELECTRICAL:

Amp Draw	208/1	208/3	240/1	240/3
L1	37	30	32	26



RM-5TCB

